

CLI

Hama Commands

Jar

Runs a jar file. Users can bundle their BSP code in a jar file and execute it using this command.

```
Usage: hama jar <jar> [mainClass] args...
```

Job

Command to interact with BSP Jobs.

```
Usage: hama job [-submit <job-file>] | [-status <job-id>] | [-kill <job-id>] | [-list [all]] | [-list-active-grooms] | [-kill-task <task-id>] | [-fail-task <task-id>]
```

-submit <job-file>	Submits the job.		
-status <job-id>	Prints the job status.		
-kill <job-id>	Kills the job.		
<ac:structured-macro ac:name="unmigrated-wiki-markup" ac:schema-version="1" ac:macro-id="8132f2b1-c52b-4469-92ad-84e8dca7dd9f"><ac:plain-text-body><![CDATA[-list [all]	-list all displays all jobs. -list displays only jobs which are yet to complete.]]></ac:plain-text-body></ac:structured-macro>
-list-active-grooms	Display the list of active groom server in the cluster.		
-list-attempt-ids <jobId> <task-state>	Displays the list of tasks for a given job currently in a particular state (running or completed).		
-kill-task <task-id>	Kills the task. Killed tasks are NOT counted against failed attempts.		
-fail-task <task-id>	Fails the task. Failed tasks are counted against failed attempts.		