

Configuration parameters

- [Configuration Keys/ Values](#)
 - [BSPJob](#)
 - [Others](#)

Configuration Keys/ Values

BSPJob

Method	Key	Default value
getWorkingDirectory()	bsp.working.dir	System prop user.dir
getBSPClass()	bsp.work.class	BSP.class
getCombinerClass()	bsp.combiner.class	Combiner.class
getNumBspTask()	bsp.peers.num	1
getJar()	bsp.jar	
	hama.supersteps.class	
getUser()	user.name	
getJobName()	bsp.job.name	
getInputFormat()	bsp.input.format.class	InputFormat.class
	hama.messenger.compression.class	BSPMessageCompressor.class
getInputKeyClass()	bsp.input.key.class	LongWritable.class
getInputValueClass()	bsp.input.value.class	Text.class
getOutputKeyClass()	bsp.output.key.class	LongWritable.class
getOutputValueClass()	bsp.output.value.class	Text.class
getMessageClass()	bsp.message.class	Text.class
getOutputPath()	bsp.output.dir	
getInputPath()	bsp.input.dir	
getOutputFormat	bsp.output.format.class	OutputFormat.class
getPartitioner()	bsp.input.partitioner.class	Partitioner.class
	bsp.checkpoint.interval	1
	bsp.tasks.max.attempts	3

Others

Class	Function	Key	Default value
JobInProgress	JobSplit	bsp.job.split.file	null
Job		bsp.sched.targets.grooms	empty array