

XsdConfigFile

.xsdconfig file

Best way to describe the the format of .xsdconfig file is to look at it's [schema](#). Documentation elements contain information on special values like ##local, ##any or *.

Examples

Rename package

```
<xb:config xmlns:xb="http://xml.apache.org/xmlbeans/2004/02/xbean/config">

  <xb:namespace uri="http://xml.apache.org/xmlbeans/2004/02/xbean/config">
    <xb:package>org.apache.xmlbeans.impl.xb.xmlconfig</xb:package>
  </xb:namespace>

</xb:config>
```

Changes the default package name of the generated classes and interfaces to the specified one.

Prefix/Suffix of generated interface names

```
<xb:config xmlns:xb="http://xml.apache.org/xmlbeans/2004/02/xbean/config"
           xmlns:ep="http://openuri.org/easypo">

  <xb:namespace uri="http://openuri.org/easypo">
    <xb:package>com.easypo</xb:package>
  </xb:namespace>

  <xb:namespace uriprefix="http://openuri.org/eas">
    <xb:prefix>Xml</xb:prefix>
  </xb:namespace>

  <xb:namespace uriprefix="http://openuri.org/easy">
    <xb:suffix>Bean</xb:suffix>
  </xb:namespace>

</xb:config>
```

Changes the names of the generated interfaces by adding the prefix and suffix.

Name change

```
<xb:config xmlns:xb="http://xml.apache.org/xmlbeans/2004/02/xbean/config"
           xmlns:jira="http://jira/xmlbeans98">
  <!--<qname> specifies a Java class name for a Qualified name -->
  <xb:qname name="jira:childElement" javaname="QNameChanged"/>
  <xb:qname name="jira:a-root" javaname="TheRoot"/>
</xb:config>
```

Changes the default name of the java interface.

Extension of generated interface

```
<xb:extension for="*">
  <xb:interface name="xmlobject.extensions.interfaceFeature.readOnlyBean.existing.IFoo">
    <xb:staticHandler>xmlobject.extensions.interfaceFeature.readOnlyBean.existing.FooHandler</xb:
staticHandler>
  </xb:interface>
</xb:extension>
```

See [ExtensionInterfacesFeature](#) for details.

- PrePost extensions*

```
<xb:config xmlns:xb="http://xml.apache.org/xmlbeans/2004/02/xbean/config">
  <xb:extension for="*">
    <xb:interface name="xmlobject.extensions.prePostFeature.readOnlyBean.existing.IFoo">
      <xb:staticHandler>
        xmlobject.extensions.prePostFeature.readOnlyBean.existing.FooHandler
      </xb:staticHandler>
    </xb:interface>
    <xb:prePostSet>
      <xb:staticHandler>
        xmlobject.extensions.prePostFeature.readOnlyBean.existing.FooHandler
      </xb:staticHandler>
    </xb:prePostSet>
  </xb:extension>
</xb:config>
```

See [PrePostSetFeature](#) for details.
