

# Installing On Windows

These instructions may change slightly with each version, so it is wise to read up on what's required each time before proceeding. Note that the configuration is slightly different in each version. You may wish to upgrade perl in conjunction with this since to do either requires disabling the processing of incoming e-mail to the e-mail server.

Information on running SpamD on Windows: [SpamdOnWindows](#)

You'll also find a pre compiled version of [SpamAssassin](#) for Windows that can simply be extracted and run here: <http://www.jam-software.com/spamassassin/>.

**Note:** The instructions below describe an obsolete procedure using tools which may no longer be available. They reportedly do not work for [SpamAssassin 3.4.1](#) using [ActivePerl 5.20.2](#). [ActivePerl](#) now seems to force the use of `dmake` for Windows and some work will likely need to be done to make [SpamAssassin](#) compatible. We are seeking a working procedure for installation on modern versions of Windows. If you can help, please send a note to the [dev list](#) to get access to edit the Wiki.

This **HISTORICAL** installation procedure is for installing [SpamAssassin](#) in native Windows (not Cygwin) using [ActivePerl](#) (Tested on [ActivePerl 5.8.9.827](#)).

1. Install or upgrade Perl if required:
  - If upgrading, make note of any modules you need to reinstall, uninstall [ActivePerl](#) and delete the /perl folder tree.
  - Download [ActivePerl](#) version 5.8.9.827 from [www.activestate.com](http://www.activestate.com).
  - Install it.
  - Get nmake from Microsoft: <http://download.microsoft.com/download/vc15/Patch/1.52/W95/EN-US/Nmake15.exe>
  - Extract the nmake.exe and nmake.err files into your /perl/bin folder
  - Use PPM to install the required perl modules:

```
ppm install Net-DNS
ppm install NetAddr-IP
```

- Use PPM to install the optional perl modules:

```
ppm repo add tcool
ppm install DB_File
ppm install Mail-SPF
ppm install IP-Country
ppm install Net-Ident
ppm install IO-Socket-INET6
ppm install IO-Socket-SSL
ppm install Encode-Detect
ppm repo add bribes
ppm install Mail-DKIM
```

2. If you want to build spamc, install Microsoft Visual C++ 6.0 or later. For instructions on getting a no-cost version see [BuildSpamcOnWindowsForFree](#). When you build [SpamAssassin](#) use a command prompt in which the VC++ environment variables are set.
3. Download the [SpamAssassin](#) zip file from [www.spamassassin.org](http://www.spamassassin.org)
4. Back up your settings if you already have it running.
5. Stop and disable [SpamAssassin](#) if it's running
6. Delete ~SpamAssassin directories, which may include:
  - c:\etc\mail\spamassassin
  - c:\perl\etc\mail\spamassassin
  - c:\perl\site\share\spamassassin
  - c:\perl\site\var\spamassassin
  - c:\perl\site\lib\mail\spamassassin.pm and spamassassin folder
  - c:\perl\site\etc\mail\spamassassin
  - c:\perl\html\site\lib\mail\spamassassin or c:\spamd\docs or wherever you put the docs last time
  - From c:\perl\bin\, delete spamassassin.\*, sa-learn.\*, sa-compile.\* and sa-update.\*
7. The following system environment variables may have to be set:
  - RES\_NAMESERVERS=<your-dns-server-ip-address>
    - If you do not set this variable, [SpamAssassin](#) should use the first DNS server in your network configuration. That is useful when, for example, you move your computer between different networks and have DNS automatically assigned. If you experience problems with domain name resolution, try setting this variable to force [SpamAssassin](#) to use the specified nameserver.
  - LANG=en\_US
    - This used to be required for [SpamAssassin](#) to work with perl 5.8.x. It should no longer be necessary, but there is no harm in having it set. If you have trouble getting [SpamAssassin](#) to run, try setting this.
8. extract the zip file (make sure your extraction tool is able to handle unix style files, [WinRAR](#) is a good choice, IZArc IS NOT!)
9. Install [SpamAssassin](#):
  - open command prompt and switch to your spamassassin source directory and type
  - perl makefile.pl
    - Answer the questions as they are asked. Remember you can NOT build spamc without a C compiler installed and its environment set up.
  - nmake
  - nmake test (this is optional)

- nmake install
- 10. Documentation should now be generated automatically by the install.
- 11. Copy the backed up configuration files into the site configuration folder, probably c:\perl\site\etc\mail\spamassassin.
- 12. Make a test folder. Copy sample-spam.txt and sample-nospam.txt to that folder.
- 13. Open a command prompt to that folder.
- 14. Type sa-update --nogpg
- 15. Test the two files. Make sure they both run fine and the spam reports on each result file are appropriate.
  - spamassassin -D -t < sample-nospam.txt > results-nospam.txt
  - spamassassin -D -t < sample-spam.txt > results-spam.txt

Once it's installed, you can edit the local.cf file in c:\perl\site\etc\mail\spamassassin. You may want to visit <http://www.rulesemporium.com> and get extra rulesets. These rulesets should also go in the c:\perl\site\etc\mail\spamassassin folder. (This assumes you've installed activeperl in c:\perl as it defaults to. If you install it somewhere else, you'll need to adjust the path accordingly.)

Note: To use sa-update with GPG, download [GPG for Windows](#), install it and add the 8.3 file path to your system path. The default path would be C:\PROGRA~1\GNU\GNUPG.

by [BretMiller](#)

modified for 3.3.1 by [DanielLemke](#)