

# Hopen

#FORMAT plain hopen(1) HADOOP hopen(1)

## NAME

hopen - open a [TaskTracker](#) to accept new tasks.

## SYNOPSIS

hopen [-h] [-jt jt1;jt2.] HOSTNAME

## DESCRIPTION

Open the [TaskTracker](#) specified by HOSTNAME. After re-opened, it will then accept new MAP/REDUCE tasks.

-h

Display usage information

-jt jobtracker url link

Specify the cluster by the jobtracker url link, for example.

-jt hostA:3479;hostB:3479 EXAMPLE

% hhosts

HOST STATUS MAX MAP REDUCE FAILURE TMP\_SPACE

c0101 ok 8 0 0 0 203M

c0102 closed 8 0 0 0 553M

% hopen c0102

Host <c0102> will be open, please confirm by hhosts/hload

% hhosts

HOST STATUS MAX MAP REDUCE FAILURE TMP\_SPACE

c0101 ok 8 0 0 0 203M

c0102 ok 8 0 0 0 553M AUTHOR

Written by Shuguang Liu

## REPORT BUGS

Report bugs to <honkliu@hotmail.com>

## COPYRIGHT

Copyright (C) 2005-2010 Shuguang Liu's Inc.

This file is not a free software, all the source codes are protected and will not be released to any body or organization without authority.

## SEE ALSO

hclose(1), hslot(1), hhosts(1), hload(1)

hopen (hadoop utils) 13.0 September 2007