

PanelGrid

Description

This is a template to describe all the [PanelGrid](#) component in a standardized way.

Screen Shot

e.g. Not a Visual Component

API

PanelGrid

component-family	javax.faces.Panel
component-type	org.apache.myfaces.HtmlPanelGrid
renderer-type	org.apache.myfaces.Grid
component-class	org.apache.myfaces.component.html.ext.HtmlPanelGrid
renderer-class	org.apache.myfaces.renderkit.html.ext.HtmlGridRenderer
tag-class	org.apache.myfaces.taglib.html.ext.HtmlPanelGridTag

PanelGroup

component-family	javax.faces.Panel
component-type	org.apache.myfaces.HtmlPanelGroup
renderer-type	org.apache.myfaces.Group
component-class	org.apache.myfaces.component.html.ext.HtmlPanelGroup
renderer-class	org.apache.myfaces.renderkit.html.ext.HtmlGroupRenderer
tag-class	org.apache.myfaces.taglib.html.ext.HtmlPanelGroupTag

Links to javadoc and tlldoc

Usage

You can use [PanelGrid](#) the same way u use the standart [UIPanel](#) component. Extensionaly you can use the colspan attribute to span cells.

Syntax

see example

Instructions

necessary?

Attributes

name	required	description
colspan	not required	how many cells should be spaned
styleClass	not required	renders a div element with a class attribute of the given styleclass around the cell content
style	not required	' _ '
*enabledOnUserRole_	not required	' _ '

visibleOnUserRole_	'_not required	* - '
---------------------	-----------------	-------

Configuration

Don't need any extra configuration.

Notes and Known issues

Some known issues like incompatibility to other frameworks/component libs

You need to use both t:panelGrid and t:panelGroup together in order to get the "colspan" function work.

Examples

Use example:

```
<t:panelGrid id="myPanel" columns="4"
footerClass="myFooterCss" headerClass="myHeaderCss" columnClasses="column1Css,column2Css,column3Css">
<f:facet name="header">
<h:outputText value="Header content here" />
</f:facet>

<h:outputText value="1" />

<t:panelGroup colspan="3" styleClass="long" >
<h:outputText value="234 one big cell" />
</t:panelGroup>

<h:outputText value="5" />
<h:outputText value="6" />
<h:outputText value="7" />
<h:outputText value="8" />

<f:facet name="footer">
<h:outputText value="Footer content here" />
</f:facet>
</t:panelGrid>
```

[Tomahawk](#)

FAQ

Post your (or potential) questions here.

Additional Information

– Keywan Ghadami <<DateTime(2008-09-17T09:00:42Z)>>