# HDFS-15547 Disk-level tiering

Uber

Leon Gao Ekanth Sethuramalingam

#### Motivation

 As HDD technology evolves in the past years, we have collected multiple types of HDD in our cluster:
 2TB disk -> 4TB -> 8TB

 We are looking forward to adopt 16TB disk in our production environment to achieve much better unit cost.

Managing disk IO across different HDDs becomes a challenge.

## Current setup

Hot blocks

4TB disk


8TB disk

- HDFS data access is highly skewed
- Read traffic contributes to 80-90% of disk IO
- Cold disks IO is almost wasted, while some hot disks are very busy.
- Need a controlled way to mix cold/hot blocks on same disk


#### Hot disk VS Cold disk

One hour disk-util average

Cold disk (Yellow) IO is almost wasted, while hot disk is busy




#### High level idea



- Control disk IO by placing hot/cold blocks on the same disk
- Use up disk space with cold blocks and at the same time keep spindles busy for different SKUs
- The ratio of hot/warm is configured from datanode level. (DISK/ARCHIVE on same disk)

## Data tiering flow on same disk without copying



#### Changes

- Able to configure DISK/ARCHIVE on same volume. Datanode should be able to control the capacity for each type and report the stats for each storage type correctly.

For example, admins can create /data01/dfs and /data01/dfs\_archive on the same mount /data01, and specify that 80% of the capacity belongs to ARCHIVE:

## Changes

- When mover tool move a block between DISK and ARCHIVE, prefer same mount and do rename instead of copy.
- (Nice to have) IO throttling on ARCHIVE portion to ensure the performance of DISK portion.
- (Nice to have) Live update ratio without restarting datanode