

VfsCapabilitiesMatrix

VFS Filesystem Capabilities Matrix

| | bz2 | ftp | gzip | http | jar | local | ram | res | sftp | smb | tar | temp | url | webdav | zip |
|-----------------------|-----|-----|------|------|-----|-------|-----|-----|------|-----|-----|------|-----|--------|-----|
| getType | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x |
| create | | x | | | | x | x | | x | x | | x | | x | |
| delete | | x | | | | x | x | | x | x | | x | | x | |
| rename | x | | | | | x | x | | x | x | | x | | x | |
| listChildren | x | x | x | | x | x | x | | x | x | x | x | x | x | x |
| readContent | x | x | x | x | x | x | x | | x | x | x | x | x | x | x |
| writeContent | x | x | x | | | x | x | | x | x | | x | | x | |
| appendContent | x | | | | | x | x | | | x | | x | | | |
| randomAccessRead | x | | x | | x | x | x | | x | x | | x | | x | |
| randomAccessWrite | | | | | | x | x | | | x | | x | | | |
| getLastModified | x | x | x | x | x | x | x | | x | x | x | x | x | x | x |
| URI | x | x | x | x | x | x | x | | x | x | x | x | x | x | x |
| compress | x | x | | | x | | | | | | | | | | x |
| attributes | | | x | x | | | | | | | | | x | | |
| virtual | | | | x | | | | | | x | | | x | | |
| fsAttributes | | | | | x | | | | | | | | | | |
| signing | | | | | | x | | | | | | | | | |
| manifestAttributes | | | | | x | | | | | | | | | | |
| setLastModifiedFile | | | | | | x | x | | x | x | | x | | | |
| setLastModifiedFolder | | | | | | x | x | | | x | | x | | | |
| dispatcher | | | | | | | x | | | | | | | | |

Legend

- `getType`: allow to determine the type (file/folder) of a entry
- `create`: create a entry
- `delete`: delete a entry
- `rename`: rename a entry
- `listChildren`: list entries below
- `readContent`: read the content of a entry
- `writeContent`: write content to a entry
- `appendContent`: append content to a already existing entry
- `randomAccessRead`: randomly read the content of a entry - allows you to set the read position within the content
- `randomAccessWrite`: randomly write the content of a entry - allows you to set the write position within the content
- `getLastModified`: get the last modification time of a entry
- `setLastModifiedFile`: allow to change the last modification time on a file
- `setLastModifiedFolder`: allow to change the last modification time on a folder
- `URI`: support URLs
- `compress`: compresses the content
- `virtual`: contains a filesystem
- `attributes`: supports file attributes
- `fsAttributes`: supports file system attributes
- `signing`: can sign file content
- `manifestAttributes`: supports the set of manifest attributes
- `dispatcher`: not a real fs implementation, just dispatches to one of the other implementations