

UsingPopupComponent

(original version in the Struts Wiki from 2006-05-26 02:52:28 by [RyanKanno](#))

From the examples/popup.jsp file in the MyFaces package, you'll find the following code snippet:

examples/popup.jsp

```
<t:popup
  styleClass="popup"
  closePopupOnExitingElement="true"
  closePopupOnExitingPopup="true"
  displayAtDistanceX="10"
  displayAtDistanceY="10" >
  <h:outputText value="This is the second textual text situation."/>
  <f:facet name="popup">
    <h:panelGroup>
      <h:panelGrid columns="1" >
        <h:outputText value="Popup Text 2"/>
      </h:panelGrid>
    </h:panelGroup>
  </f:facet>
</t:popup>
```

In a [ShaleClay](#) configuration file, it would look like the following:

```
{{{
...
<view>
...
<component...>
...
<element renderId="2" jsfid="t.popup">
<attributes>
<set name="styleClass" value="popup"/>
<set name="closePopupOnExitingElement" value="true"/>
<set name="closePopupOnExitingPopup" value="true"/>
<set name="displayAtDistanceX" value="10"/>
<set name="displayAtDistanceY" value="10"/>
</attributes>
<element renderId="1" jsfid="outputText">
<attributes>
<set name="value" value="This is the second textual text situation." />
</attributes>
</element>
<element renderId="2" jsfid="panelGroup" facetName="popup" >
<element renderId="1" jsfid="panelGrid">
<attributes>
<set name="columns" value="1"/>
</attributes>
<element renderId="1" jsfid="outputText">
<attributes>
<set name="value" value="Popup Text 2" />
</attributes>
</element>
</element>
</element>
</element>
...
</component...>

...
</view>
...
}}
```