

# XsdConfigFile

## .xsdconfig file

Best way to describe the the format of .xsdconfig file is to look at it's [schema](#). Documentation elements contain information on special values like ##local, ##any or \*.

## Examples

### Rename package

```
<xb:config xmlns:xb="http://xml.apache.org/xmlbeans/2004/02/xbean/config">

    <xb:namespace uri="http://xml.apache.org/xmlbeans/2004/02/xbean/config">
        <xb:package>org.apache.xmlbeans.impl.xb.xmlconfig</xb:package>
    </xb:namespace>

</xb:config>
```

Changes the default package name of the generated classes and interfaces to the specified one.

### Prefix/Suffix of generated interface names

```
<xb:config xmlns:xb="http://xml.apache.org/xmlbeans/2004/02/xbean/config"
            xmlns:ep="http://openuri.org/easypo">

    <xb:namespace uri="http://openuri.org/easypo">
        <xb:package>com.easypo</xb:package>
    </xb:namespace>

    <xb:namespace uriprefix="http://openuri.org/eas">
        <xb:prefix>Xml</xb:prefix>
    </xb:namespace>

    <xb:namespace uriprefix="http://openuri.org/easy">
        <xb:suffix>Bean</xb:suffix>
    </xb:namespace>

</xb:config>
```

Changes the names of the generated interfaces by adding the prefix and suffix.

### Name change

```
<xb:config xmlns:xb="http://xml.apache.org/xmlbeans/2004/02/xbean/config"
            xmlns:jira="http://jira/xmlbeans98">
    <!--<qname> specifies a Java class name for a Qualified name -->
    <xb:qname name="jira:childElement" javaname="QNameChanged"/>
    <xb:qname name="jira:a-root" javaname="TheRoot"/>
</xb:config>
```

Changes the default name of the java interface.

### Extension of generated interface

```
<xb:extension for="*">
    <xb:interface name="xmlobject.extensions.interfaceFeature.readOnlyBean.existing.IFoo">
        <xb:staticHandler>xmlobject.extensions.interfaceFeature.readOnlyBean.existing.FooHandler</xb:
staticHandler>
    </xb:interface>
</xb:extension>
```

See [ExtensionInterfacesFeature](#) for details.

---

- **PrePost extensions\***

```
<xb:config xmlns:xb="http://xml.apache.org/xmlbeans/2004/02/xbean/config">
    <xb:extension for="*">
        <xb:interface name="xmlobjext.extensions.prePostFeature.readOnlyBean.existing.IFoo">
            <xb:staticHandler>
                xmlobjext.extensions.prePostFeature.readOnlyBean.existing.FooHandler
            </xb:staticHandler>
        </xb:interface>
        <xb:prePostSet>
            <xb:staticHandler>
                xmlobjext.extensions.prePostFeature.readOnlyBean.existing.FooHandler
            </xb:staticHandler>
        </xb:prePostSet>
    </xb:extension>
</xb:config>
```

---

See [PrePostSetFeature](#) for details.