

Stress Tests

Launching Stress Tests

1. There is approximate list of commands that should be executed:

```
cd <new folder for bti>
svn co https://svn.apache.org/repos/asf/harmony/enhanced/buildtest/trunk/infra
cd infra
ant -Dtest.suites="stress" install
ant -Dtest.suites="stress" setup
ant -Dtest.suites="stress" run
```

Results could be observed at build/results/stress folder

2. In case of testing virtual machine in different location the following commands can help:

```
cd <new folder for bti>
svn co https://svn.apache.org/repos/asf/harmony/enhanced/buildtest/trunk/infra
cd infra
ant -Dtest.suites=stress install
ant -Dtest.suites=stress setup
```

Modify file "required-parameters.properties" in order to set the path to tested vm like:

```
stress.jvm.under.test=C:\harmony-jdk-628209\jre\bin\java.exe
```

Start test running

```
ant -Dtest.suites=stress run
```

To launch stress tests without buildtest do the following:

1. Download required files from a repository.

```
svn co http://svn.apache.org/repos/asf/harmony/enhanced/buildtest/branches/2.0/tests/stress
svn co http://svn.apache.org/repos/asf/harmony/enhanced/buildtest/branches/2.0/tests/tools
```

2. Follow instructions from stress/README.txt.
3. Build and run the tests.

```
cd stress/qa && ant update && ant
```

Also it's useful to keep in mind the following:

1. On Linux you might want to use `ant --noconfig` to make additional ant packages work.
2. On Windows `SystemRoot` property in this capitalization should be set to `/windows` or `/winnt` directories which contain the OS distribution.
3. You might want to double check that `TestedRuntime` property at `stress/qa/config/cfg_env.xml` is set to a path to a java executable you want to test.
4. You may excluding more tests by adding their IDs to `stress/qa/config/exclude.file`.
5. When running as a part of BTI you need to remove `build/classes/stress/setup`. OK if you want to rebuild the test suite.

Stress Tests TODO

P1

1. Fix stack walking tests by catching [OutOfMemoryErrors](#) properly.
2. Fix class loading tests by adjusting timeout automatically.

P2

1. Rename `qa/src/test/stress/org/apache/harmony/test/stress/<module>/<submodule>/<test>/<testcase>.xml` to `src/org/apache/harmony/test/stress/<module>/<submodule>/<testcase>.xml`, or even `src/<module>/<submodule>/<testcase>.xml`. Cannot do this now and cannot be silent about it.