

JEditTemplate

To install, add the velocity.xml to one of your 'mode' directories, and add the following to that directory's catalog file :

```
<MODE NAME="velocity" FILE="velocity.xml"
      FILE_NAME_GLOB="*.vw" />
```

and restart JEdit. If there are any problems with installation, see the JEdit documentation about 'Modes'.

velocity.xml:

```
<?xml version="1.0"?>

<!DOCTYPE MODE SYSTEM "xmode.dtd">

<MODE>
    <PROPS>
        <PROPERTY NAME="commentStart" VALUE="##" />
        <PROPERTY NAME="commentEnd" VALUE="##" />
        <PROPERTY NAME="lineComment" VALUE="###" />
    </PROPS>
    <RULES IGNORE_CASE="TRUE">
        <!-- whitespace: (space and tab) -->
        <WHITESPACE> </WHITESPACE>
        <WHITESPACE> </WHITESPACE>

        <!-- SGML comment -->
        <SPAN TYPE="COMMENT1">
            <BEGIN>&lt;!--</BEGIN>
            <END>--&gt;</END>

        </SPAN>

        <!-- JavaScript -->
        <SPAN TYPE="MARKUP" DELEGATE="javascript::MAIN">
            <BEGIN>&lt;SCRIPT&gt;</BEGIN>
            <END>&lt;/SCRIPT&gt;</END>

        </SPAN>

        <!-- stylesheet -->
        <SPAN TYPE="MARKUP" DELEGATE="css::MAIN">
            <BEGIN>&lt;STYLE&gt;</BEGIN>
            <END>&lt;/STYLE&gt;</END>

        </SPAN>

        <!-- DTD instructions -->
        <SPAN TYPE="KEYWORD2" DELEGATE="xml::DTD-TAGS">
            <BEGIN>&lt;!--</BEGIN>
            <END>&gt;</END>

        </SPAN>

        <KEYWORDS>
            <KEYWORD1>#set</KEYWORD1>
            <KEYWORD1>#foreach</KEYWORD1>
            <KEYWORD1>#end</KEYWORD1>
            <KEYWORD1>#if</KEYWORD1>
            <KEYWORD1>#else</KEYWORD1>
            <KEYWORD1>#elseif</KEYWORD1>
            <KEYWORD1>#parse</KEYWORD1>
            <KEYWORD1>#macro</KEYWORD1>
            <KEYWORD1>#stop</KEYWORD1>
            <KEYWORD1>#include</KEYWORD1>
        </KEYWORDS>

        <MARK_FOLLOWING TYPE="KEYWORD2">${</MARK_FOLLOWING>

        <!-- markup tags -->
        <SPAN TYPE="MARKUP" DELEGATE="TAGS">
```

```
        <BEGIN>&lt; </BEGIN>
        <END>&gt; </END>
    </SPAN>

    <!-- SGML entities -->
    <SPAN TYPE="LITERAL2" NO_WORD_BREAK="TRUE">
        <BEGIN>&amp; </BEGIN>
        <END>; </END>
    </SPAN>
</RULES>

<RULES SET="TAGS" DEFAULT="MARKUP">
    <!-- whitespace: (space and tab) -->
    <WHITESPACE> </WHITESPACE>
    <WHITESPACE>          </WHITESPACE>

    <SPAN TYPE="LITERAL1">
        <BEGIN>" </BEGIN>
        <END>" </END>
    </SPAN>

    <SPAN TYPE="LITERAL1">
        <BEGIN>' </BEGIN>
        <END>' </END>
    </SPAN>

    <SEQ TYPE="OPERATOR">=</SEQ>
</RULES>
</MODE>
```