

FAQs

FAQs

Buttons are not working (Linux only).

In version 2.28, Gnome has been changed to use client-side windows. This could cause that some GUI widgets (buttons, trees) in Apache Directory Studio won't work as expected. If you encounter any problems set the environment variable GDK_NATIVE_WINDOWS to true before starting Studio:

```
GDK_NATIVE_WINDOWS=1 ./ApacheDirectoryStudio
```

More information could be found at https://bugs.eclipse.org/bugs/show_bug.cgi?id=291257

How to set the language of Studio?

Studio currently is translated in three languages: English (en), French (fr) and German (de). When starting Studio, the language setting of your operation system is used to determine the language of Studio (On linux, the LC_CTYPE environment variable is used to determinate the default language). However it is possible to force another language:

The first option is to start Apache Directory Studio with the following command line parameters:

- On Linux:

```
./ApacheDirectoryStudio -nl en
```

- On Windows:

```
"Apache Directory Studio.exe" -nl en
```

The second option is to create a file *Apache Directory Studio.ini* (for Windows) or *ApacheDirectoryStudio.ini* (for Mac OS X and Linux) in Studio's installation directory (for Mac OS X the correct location is *Apache Directory Studio/Contents/MacOS*) with the following content:

```
-nl  
en
```

Please notice the line break between -nl and the language.

When creating a new connection I get the part of the wizard which allows me to "You can specify additional connection parameters". Buttons back, next and finish are disabled. Basically now way to add a new connection.

This is an issue of release 1.0.0 and 1.0.1. It will be fixed in the next release 1.1.0. There is a workaround: Uncheck the "Get base DN's from Root DSE" check box, the 'Next' button will be activated.

When browsing and expanding an entry, Studio only shows 1000 child entries.

Studio uses a client-side count limit when browsing the DIT. This limit is defined in the connection properties. See [Connection Properties](#) how to change it.

How to set the Java VM to use?

The first option is to start Apache Directory Studio with the following command line parameters:

- On Linux:

```
./ApacheDirectoryStudio -vm <path to java executable>
```

- On Windows:

```
"Apache Directory Studio.exe" -vm <path to java executable>
```

The second option is to create a file *Apache Directory Studio.ini* (for Windows) or *ApacheDirectoryStudio.ini* (for Mac OS X and Linux) in Studio's installation directory (for Mac OS X the correct location is *Apache Directory Studio/Contents/MacOS*) with the following content:

```
-vm  
<path to java executable>
```

Please notice the line break between -vm and the path.

How to increase the heap memory?

The first option is to start Apache Directory Studio with the following command line parameters:

- On Linux:

```
./ApacheDirectoryStudio -vmargs -Xms128m -Xmx512m -XX:PermSize=128m -XX:MaxPermSize=128m
```

- On Windows:

```
"Apache Directory Studio.exe" -vmargs -Xms128m -Xmx512m -XX:PermSize=128m -XX:MaxPermSize=128m
```

The second option is to create a file *Apache Directory Studio.ini* (for Windows) or *ApacheDirectoryStudio.ini* (for Mac OS X and Linux) in Studio's installation directory (for Mac OS X the correct location is *Apache Directory Studio/Contents/MacOS*) with the following content:

```
-vmargs  
-Xms128m  
-Xmx512m  
-XX:PermSize=128m  
-XX:MaxPermSize=128m
```

Please notice the line breaks.

Location of Apache Directory Studio settings

The settings are located per default in your home directory under the directory *.ApacheDirectoryStudio*.

The file containing all connections is

```
.ApacheDirectoryStudio/.metadata/.plugins/org.apache.directory.studio.connection.core/connections.xml
```

The file containing all searches and bookmarks is

```
.ApacheDirectoryStudio/.metadata/.plugins/org.apache.directory.studio.ldapbrowser.core/browserconnections.xml
```

The file containing the history of the connection wizard (recently used hosts and bind users) is

```
.ApacheDirectoryStudio/.metadata/.plugins/org.apache.directory.studio.connection.ui/dialog_settings.xml
```

The file containing the history of search settings (recently used DN's, filters, returning attributes) is

```
.ApacheDirectoryStudio/.metadata/.plugins/org.apache.directory.studio.ldapbrowser.common/dialog_settings.xml
```

There are some more *dialog_settings.xml* files in the other plugins directories.

BTW: the location of the settings directory could be configured by changing the parameter "osgi.instance.area.default" in configuration/config.ini.